



Product highlights

- * Multilingual operation
- * Automatic built in test and self diagnosis
- * Secure access Key
- * Threat alert and material classification
- * Auto archiving
- * Energy saving design
- * One key turn off
- * Drugs and explosives inspection
- * Indication of the date and time
- * Baggage counter

X-ray Generator (single)

Anode Voltage	140 KV
Ray direction	Downward
Cooling / Duty Cycle	Sealed oil cooling /100%
Operating Environment	
Operation temperature/Humidity	5°C-40°C / 0%-90%(non-condensing)
Storage Temperature/Humidity	-20°Cto 60°C / 10%-90%(non-condensing)
Operation Power	220VAC(±10%) 50±3Hz (Options: 110-120V, 230-240V, 60Hz)
Stabilizer and UPS	Optional

General specifications

General Specifications	
Tunnel size(mm)	800(L)*650(W)
Conveyor Speed(m/s)	0.4
Conveyor height(mm)	305
Conveyor Max Load(kgs)	200
X ray dose/inspection	≤3.0 μGy
X ray leakage	<1μGy/h at any point 5 centimeters outside the external surface
Penetration	39mm steel
Wire Resolution	AWG36
Spatial resolution	Horizontal:dia 1.6mm, Vertical: dia 1.6mm
Power Consumption	max. 1KW
Noise	<60 dB
Film Safety	Guarantee ASA/ISO1600 Film
Imaging System	
X-ray Sensor	L-Shaped Photodiode Array, 12bit deep
Images process	24bit real time processing ,4colors analysis, Images displayed marked date and ID No., Count the number of bags
Image display	High resolution of 1920*1080 pixel; Image Grey Level: 65536
Image Enhancement	1-32 times enlargement continuity, Color/BW, negative, high/low penetration enhancement, brightening, darkening, gray level scan, super enhancement, elimination of organics/inorganics, local enhancement, pseudo color processing, edge enhancement, etc.
Explosives & Narcotics Detection	Suspicious organics highlight(atomic number Zeff=7,8,9)
Suspicious Alarm	Alarm and box line the suspicious objects including hard to penetrate material, explosives and drugs
Threat Image Projection(TIP)	Inserting fictional, but realistic images of threat items into baggage during screening operation, for maintenance of vigilance, as well as training and assessment of image identification capability
Image Recall	30 images recallable
Image Archive	Up to 100,000 images stored automatically, enable transferring to USB disk, and converting to JPG format
Miscellaneous Functions	Time/date display, counters, user management, system-on/X-ray-on timers, power on self test, built-in diagnostic facilities, dual-direction scanning, system log, system standby and stimulant training, etc.
Options	Intelligent roller, network, etc.

Computer and other	
Monitor	One 21.5-inch LCD monitor, 1920*1080, one console desk
RAM	1GB
Hard Disk	250G
Keyboard	Special designed
System	Embedded Linux operating system, multi core ARM, stable and reliable
Electric roller	Three-phase
Compliance	
International	* ISO19001; ISO14001; ISO45001 * CE RoHS * FDA FCC
Physical Specifications	
Unit weight (kgs)	350
Unit size (mm)	2935(L)*1050(W)*1300(H)
after packed in wooden pallet -	
Gross weight (kgs)	500
Packing size	#1: 185*120*152cm #2: 75*65*99cm

Dimensions

