

General specifications

Parameters	
Material	IP69 water proof Food grade Belt
Accuracy	+/-1-2g
Weighing Range	1-3000g
Minimum Scale	1g
Belt Dimension	As drawing
Throughput	60-120pcs/min(adjustable)
Reject Section	7 arms
Additional Function	Network interface, USB output.
Flow Direction	From left to right
Belt height from ground:	750mm(+/-50mm adjustment)
Display size	10inch.(Full touch screen)
Suggested Product Dimension (L) (W)	≤400mm * 250mm
Machine weight	300KG
With stainless steel	304 table



Product Highlight

Customizable

- The number of grades can be customized (even number)
- Touch screen with waterproof cover. (optional)
- Multiple languages available.

Efficient and Economical

- The lane adopts the chain conveyor belt, which has a long service life.
- The material is challenging to slide and fall during transmission.
- With high-precision digital sensors, the sampling speed is fast, and the highest precision is stable at $\pm 2g$

Easy Maintenance

- The conveyor is easy to disassemble.
- All stainless steel 304 construction.
- Professional water proof and resistant to seawater corrosion

User Friendly

- Auto learning function. Store 100 product settings.
- Easily connect with printer, labeling machine, etc.
- Data can be stored up to 1 year, and can be exported in .xls file, saved to USB flash disk.(Optional)



Application:

Beef, fish fillets, whole fish, whole chicken, steaks, lobsters, etc.



Measurement

